



## COSHH Reports - CCF 2-IN-1 Multi Sealant

CCF Multi Sealant is an aqueous acrylic emulsion with high density mineral fillers. No component labeled as dangerous under EEC directives criteria.

### Composition: Hazardous ingredients

Non hazardous. Prolonged exposure to the product may produce minor skin irritation

### Prime Hazards

None

### First Aid Measures:

**Eye contact:** Flush with copious quantities of fresh water for 15 minutes.

**Skin Contact:** Discard contaminated clothing. Wash skin with soap and water.

**Inhalation:** May cause irritation. Remove patient to fresh air.

**Ingestion:** Ingestion of small quantities is unlikely to cause significant reaction. Do not induce vomiting because of the risk of fluid entering the lungs. Wash out mouth and give plenty of water to drink. Seek medical attention.

### Firefighting Measures:

CCF Multi Sealant is non flammable but packaging can burn.

**Suitable extinguishing media:** Water spray, dry powder, foam and carbon dioxide

**Unsuitable Extinguishing media:** none

**Special exposure standards:** None

### Leak and Spill Procedure:

If dry, dispose of as non hazardous waste.

If wet, absorb with sand or non flammable absorbent material and dispose of after curing as a non hazardous waste.

**Method of clean up:** Take up mechanically

### **Handling and Storage:**

Do not eat or drink during use. Observe good industrial hygiene.

Store for short periods on work site in unopened containers between 5°C and 40°C clear of the ground.

### **Personal protection & exposure controls:**

Rubber gloves, a light dust mask and goggles should be worn.

### **Physical Data:**

**Appearance:** Off white thixotropic paste.

**Odour:** Faintly aromatic

**ph:** 8

**Viscosity:** 7000-1000 poise at 20°C

**Specific Gravity:** 1.47 at 20°C

**Solubility:** Miscible with water.

### **Stability & Reactivity Data**

#### **Chemically stable:**

Not reactive with other substances

Shelf life 12 months stored internally between 5°C and 30°C

### **Ecological Information:**

Do not allow to enter drains because of the danger of blockage. Otherwise non hazardous.

### **Waste Disposal:**

Dispose of as general waste at an approved waste site suitable for building waste, observing local regulations.

### **Transport Information:**

Not classified as hazardous.

CHIP 2 not applicable

### **Other information:**

To be used as a fire and acoustic seal between wood, block, concrete, drylining and brickwork in interior or external construction.

